

# Safegrip® GRP BOARDS



Kapellskjär, Sweden



1.



2.



3.

## DESCRIPTION

Safegrip® GRP Boards are based on glass reinforced polyester boards coated with Safegrip® EP 7080 TX dressed with Dynagrip. Safegrip® GRP Boards is suitable for all kinds of gangways. It can also occasionally take the traffic of a light vehicle.

## ADVANTAGES

- Light in weight
- Very quick to install
- No curingtime, are ready for traffic immediately

## SPECIFICATION

Weight:	About 11 kg/m <sup>2</sup>
	+ antiskid coating
Size:	Width 0,70 m
	Length up to about 10m
	Thickness 20 mm
Load:	Fully supported 1000 kg/m <sup>2</sup>
	Support with cc 600 mm 700 kg/m <sup>2</sup>
Service-temperature	- 20 to + 50°C

## APPLICATION

- Existing floor should be cleaned.
- Lay down the first board with the "she" side pointing to where the next board is to be connected.
- Insert the "he" side of the next board at an angel of about 30° and press it gently while you lower it. See the three pictures at the left.
- Be sure that they are well locked and that the joint between is no more than 1 mm.
- If you have to cut the panels the best tool is an angelgrinder with a diamond disk.

## TECHNICAL SERVICE

Fjerby AS is at your disposal regarding technical questions and the use of Safegrip® GRP Boards. .

All the data and suggestions in this datasheet is based on tests and experiences. As the users working conditions is out of our control, we cannot take the responsibility for the result that the user obtains by using the product.