

Safeclean HD October 2005

Degreasing agent.

DESCRIPTION

Auto Extra is a degreasing agent that will clean a substrate from normal grease, oil, diesel, dirt from smoke etc.

ADVANTAGES

Auto Extra is an environmental friendly product that will be broken down in the nature. It is easy to use.

SPECIFICATIONS

Gravity weight	1,06
Boiling point	100°C
PH	11,5
Solubility in water	100%
Viscosity	26 cP

DILUTIONS

Extremely dirty	1 : 5 (Auto Extra : Water)
Dirty	1 : 10
Light dirty	1 : 20

TEMPERATURE LIMITATIONS

All work has to be done above 0°C. At low temperatures the effect to clean is poorer. Best results are achieved at 20°C and above.

CLEANING INSTRUCTIONS

1. Pour the amount of Auto Extra into a bucket of clean water.
Choose the concentration from the above table.
2. Give it a quick stir.
3. Either pour it in a low-pressure spray equipment or pour it straight on the surface to be cleaned.
4. Let the solution work for 5 minutes. If it dries in spots pour on more.
5. Give it a light scrub with a soft brush
6. Use a high-pressure washer to rinse off the solution.
7. If there is spots that are not clean after this operation, you should increase the concentration of Auto Extra and repeat the procedure.

PACKING

The Auto Extra is supplied in plastic containers of 25 l.

STORAGE

The Auto Extra shall be stored frost free. The shelf life is minimum 1 year if kept in the container with the lid tightly closed.

HEALTH AND SAFETY

Please see our health and safety datasheet.

TECHNICAL SERVICE

Please contact Fjerby for further information if necessary.

All the data and suggestions in this datasheet are based on tests and experiences. As the users working conditions is out of our control, we cannot take the responsibility for the results that the user obtains by using the product.